



**PROBoardMAX** is fire rated 105 mil thick extreme duty water proof floor protection for very demanding job-site conditions.

PROBoardMAX is designed specifically for the CONSTRUCTION PROFESSIONAL and provides superior protection against impacts, spills and punctures.



**FEATURES**

Fire Rated	100% Recyclable
Tru-Lay Flat Sheets	Non - Abrasive
Non-Staining	Patented
LEED Compliant	Made in USA

**SIZES**

4'x6' (48in x 72in) and 4'x8' (48in x 96in)

**APPLICATIONS**

Construction	Clean Rooms
Maintenance	Health Care Facilities

**INSTRUCTIONS**

Clean surface well before installation. Align PROBoardMAX edge to edge. Tape along seams. Cut to fit with utility knife. **DO NOT** use on curing floors. **DO NOT** tape directly to floor. If running machinery stagger sheets like brickwork. To clean use slightly damp mop.

**PRODUCT SPECIFICATIONS**

Thickness	105 mil
Fire Rated	ASTM E648 Class II
Material	100% recycled laminated paperboard HDPE/LDPE surface
Weight/Sheet	9lbs/12lbs
Size	4'x6' & 4'x8'
Density (lbs / 1000 sq. ft)	378
Density (Kg/M3 cubic meter)	697
Ph	Neutral
Color	White
Inks/Dyes	No
Country of Origin	USA
LEED Compliant	Yes
Recyclable	100%
Vapor Permeable	No
Water Proof	Yes

All information contained in this document was obtained from sources that PROTEX® Products (PROTEX) believes reliable and is provided for guidance by experienced industry professionals. This information is provided without any implied or expressed warranty regarding merchantability of fitness, completeness, or accuracy. As conditions, usage, application, and installation are beyond our control, PROTEX shall not be liable for any direct, indirect, consequential or punitive damages in any way related to the above mentioned information or to the handling, storage, use, performance or disposal of the product. PROTEX Products' entire liability is strictly limited to the invoice price of product paid. Final determination of the suitability of any material or product is the sole responsibility of the user.