

PROTEX is designed to be an option to roll products and at 54 mil - is 40% THICKER than the roll products.

PROTEX is designed specifically for the CONSTRUCTION PROFESSIONAL and provides superior protection against impacts, spills and punctures.

Tru-Lay-Flat sheets are non-staining and vapor permeable.





FEATURES

Fire Rated 100% Recyclable
Vapor Permeable Easy Install & Removal
Tru-Lay Flat Sheets
Non-Staining Patented
LEED Compliant Made in USA

SIZES

4'x6' (48in x 72in) and 4'x8' (48in x 96in)

APPLICATIONS

Construction Remodeling Maintenance Tenant Improvements

INSTRUCTIONS

Clean surface well before installation. Align PROTEX edge to edge. Tape along seams. Cut to fit with utility knife. If floor is still curing DO NOT overlap or tape. DO NOT tape directly to floor. If running machinery/equipment stagger sheets like brickwork.

PRODUCT SPECIFICATIONS

Thickness 54 mil
Fire Rated ASTM E648 Class II
Material 100% recycled

laminated paperboard

Weight/Sheet 4.5lbs/6lb Size 4'x6' & 4'x8'

Density (lbs/1000 sq. ft) 189 Density (Kg/M3 cubic meter) 656 Ph Neutral Color Natural Inks/Dyes No Country of Origin USA **LEED Compliant** Yes Recyclable 100% Vapor Permeable Yes

All information contained in this document was obtained from sources that PROTEX* Products (PROTEX) believes reliable and is provided for guidance by experienced industry professionals. This information is provided without any implied or expressed warranty regarding merchantability of fitness, completeness, or accuracy. As conditions, usage, application, and installation are beyond our control, PROTEX shall not be liable for any direct, indirect, consequential or punitive damages in any way related to the above mentioned information or to the handling, storage, use, performance or disposal of the product. PROTEX Products' entire liability is strictly limited to the invoice price of product paid. Final determination of the suitability of any material or product is the sole responsibility of the user.



